



**ALL TRADES MANUFACTURING PTY LTD**  
UNIT 11/5 HUDSON AVENUE, CASTLE HILL NSW 2154  
PH – 02 8850 2700      FAX 02 8850 2701  
[www.all-trades.com.au](http://www.all-trades.com.au)      email; [sales@all-trades.com.au](mailto:sales@all-trades.com.au)

ABN: 27363290799

**"A-Z Product Solutions for Trade and Industry"**

### **OCCUPIED TRENCH ROLLER**

The shape of the base section on our Occupied Trench Roller allows for conduit or obstacles to be cleared whilst the “catamaran” style base provides a firm purchase onto the surrounding ground.

The 140mm alloy bearing roller is housed in the frame via a heavy duty bolt and lock nut, which also serves as the axle for the unit.

In most circumstances the maximum span between rollers would be 3 metres or less. This would depend on factors such as cable diameter, cable sag issues, ground condition etc. The individual bearings in the Occupied Trench Roller will accommodate loads in excess of 200kg.

Although designed for occupied trenches, the unit performs just as well in flat or unoccupied trenches.

- Length: 300mm
- Width: ( Including frame ) 200mm
- Height: ( To running surface of roller ) 160mm
- Maximum cable diameter: 138mm
- Weight: 4.0kg

